

<b>Test Code Sheet Number</b>	<b>2</b>	<b>2</b>	<b>1</b>	<b>3</b>	<b>13</b>
-------------------------------	----------	----------	----------	----------	-----------

TEST CODE SHEET

---

**1. TYPE OF TEST(S)**

Pressure differential at valve closure.

**2. WATER REGULATIONS REQUIREMENTS FOR FITTINGS**

Schedule 2

15-(1) .... every water system shall contain an adequate device or devices for preventing backflow of fluid from any appliance, fitting or process from occurring.

**3. BRITISH STANDARDS OR WATER SPECIFICATION, DEEMED TO SATISFY WATER REGULATIONS REQUIREMENTS**

3.1 Fittings with 'kitemarks' which are deemed to satisfy the requirements of regulations are listed in the directory.

**4. TEST PROCEDURE**

Note Unless otherwise stated the temperature of the test fluid shall be  $20 \pm 10^{\circ}\text{C}$ .

4.1 Tests applicable to the following:-

**CHECK VALVES**

DN 6 to DN250.

Devices for the prevention of contamination by backflow.

---

(A) **CHECK VALVES** (Derived from prEN 164167. Clause 7.5)  
DN 6 to DN250.

**TEST METHOD**

**APPARATUS** The following apparatus is required.

A supply of water to achieve the test flow rates at the required pressure.

Sight glass.

Scale rule, graduated in mm.

Pressure gauges.

Control valves.

The example of the test equipment shown in Figure 15 is for guidance only.

Laboratory equipment must be designed to ensure that the valve can be tested to verify the requirement.

**NOTE:** For double check valves each single check valve shall be tested separately. The check valve not being tested shall be either removed or the valve held in the open position.

**PROCEDURE** The procedure shall be as follows:-

(1) Mount the device in the test system in its normal working position. (Reference Figure 15).

